Technical specification

- **1 Ceiling** upholstered, equipped with lighting and exhaust fans
- **2 Upholstered wall** full, 3" (75 mm) thick, upholstered on both sides, acoustic filling with sound isolation properties
- **3** Columns 3" x 3" (75 x 75 mm), powder coated
- Shelf 4/8" / 12 mm MDF, colour: black, can be mounted only to upholstered walls with 39 3/8" / 1000mm width.
- 5 Aluminum strips 2/8" (5 mm) thick
 6 Glass wall toughened glass, 2/8" (6 mm) thick
- Glass wair toughened glass, 2/8 (6 mm) thick
 Glass door toughened glass, 3/8" (8 mm) thick, equipped with hinges, handle with a lock and gaskets system improving the acoustic properties of the booth
- 8 Floor melamine plate + acoustic covering (7/8" / 21mm thickness), colour: graphite - option with additional fee
- 9 Fans:
- in take (near the floor) can be turned on and off, with adjustable fan speed. The exact location can be found on the shop drawings.
- •exhaust integrated with the ceiling lamp









Hako

mdd.eu

Configuration examples

HK03







Dimensions (inch/mm)	Mediabox location	
1 Mediabox - 2x110V + 1xUSB + 1xUSB type C A - on the left wall near the floor B - on the right wall near the floor C - on the shorter wall above 740mm height Legend:	A, B 49 2/8" (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250) (1250)	C 39 3/8" (1000) (49) (48) (48) (48) (48) (48) (48) (48) (48



49 2/8" (1250) 55 1/8" (1400) HK021



НК04





Dimensions (inch/mm)

Legend:

in - take fans (near the floor) can be turned on and off, with adjustable fan speed. - Attention! It is suggested not to block fans to ensure the proper airflow rate

motion sensor (activates the exhaust fans and lighting)

 $\textcircled{\ensuremath{\mathbb{B}}}$ wireless light switch - which can be situated in any place

 $\mathbf{E}_{\mathbf{y}}$ exhaust fans are integrated with the ceiling lamp





Dimensions (inch/mm)

Legend:

in - take fans (near the floor) can be turned on and off, with adjustable fan speed. - Attention! It is suggested not to block fans to ensure the proper airflow rate

 $\overset{\textcircled{1}}{\boxplus}$ wireless light switch - which can be situated in any place

 $\underline{\underline{\mathbf{x}}}_{\underline{v}}$ exhaust fans are integrated with the ceiling lamp

НК06





Dimensions (inch/mm)

Legend:

in - take fans (near the floor) can be turned on and off, with adjustable fan speed. - Attention! It is suggested not to block fans to ensure the proper airflow rate

motion sensor (activates the exhaust fans and lighting)

(i) wireless light switch - which can be situated in any place exhaust fans are integrated with the ceiling lamp

HK07





